Product Information Sheet

Colour-tuneable light source:

High luminance light source:

Anti-glare shield:

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria						
Lighting technology used:	LED	Non-directional o	r NDLS			
Light source cap-type	Leads					
(or other electric interface)						
Mains or non-mains:	NMLS	Connected ligh	t No			

Product parameters

No

No

No

source (CLS):

Envelope:

Dimmable:

Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
<u> </u>	mption in on- 00 h), rounded st integer	12	Energy efficiency class	E			
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	1 368 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000			
On-mode pow pressed in W	ver (P _{on}), ex-	11,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00			
(P _{net}) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80			
Outer dimen-	Height	125	Spectral power dis-	See image			
sions without separate con- trol gear, light- ing control	Width Depth	260 55	tribution in the range 250 nm to 800 nm, at full-load	in last page			

No

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,438		
		nates (x and y)	0,403		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	11	Survival factor	1,00		
the lumen maintenance factor	0,96				

(a)'-': not applicable; (b)'-': not applicable;

